


Appln No. 09/522,185

Amdt date June 15, 2004


Reply to Office action of March 31, 2004

**Amendments to the Specification:**

Please replace the paragraph beginning on page 9, line 17 with the following rewritten paragraph:

The DSP server 25 includes a resource manager 24 which receives commands from, forwards events to, and exchanges data with the user application layer 26. The user application layer 26 can either be resident on the DSP 17 or alternatively on the host 21 (see FIG. 2), such as a microcontroller. An application programming interface 27 28 (API) provides a software interface between the user application layer 26 and the resource manager 24. The resource manager 24 manages the internal / external program and data memory of the DSP 17. In addition the resource manager dynamically allocates DSP resources, performs command routing as well as other general purpose functions.

Please replace the paragraph beginning on page 12, line 5 with the following rewritten paragraph:

In the fax relay mode 40, the resource manager invokes a fax exchange 52 service. The packet fax exchange 52 may employ various data pumps including, among others, V.17 which can operate up to 14,400 bits per second, V.29 which uses a 1700-Hz ~~earrer~~ carrier that is varied in both phase and amplitude, resulting in 16 combinations of 8 phases and 4 amplitudes which can operate up to 9600 bit per second, and V.27ter which can operate up to 4800 bits per second. Likewise, the resource manager invokes a packet data exchange 54 service in the data relay mode 42. The packet modem data exchange ~~52~~ 54 may employ various data pumps including, among others, V.22bis/V.22 with data rates up to 2400 bits per second, V.32bis/V.32 which enables full-duplex transmission at 14,400 bits per second, and

**Appln No. 09/522,185**

**Amdt date June 15, 2004**

**Reply to Office action of March 31, 2004**

*22*  
*Revised*  
V.34 which operates up to 33,600 bits per second. The ITU Recommendations setting forth the standards for the foregoing data pumps are incorporated herein by reference as if set forth in full.

---